

LISTING OF CLAIMS

The present listing of claims replaces all prior versions.

Claim 1. (currently amended) A modeling method for defining software applications by a developer using a visualizable computer executable modeling language, said method comprising:

providing a plurality of display elements for displaying screen objects on a display screen;

displaying components corresponding to said screen objects;

defining each of the software applications as a hierarchy of process models, input and output slots, data models and flow rules;

classifying some of said process models and said data models as atomic;

classifying all other process models and data models as composite;

defining each of said composite process models as a construction of at least one of sub process models, slots, data models and flow rules;

defining a portion of said input slots as having one of the following sub-classifications:

mandatory; and

optional, wherein a process that requires input at its mandatory input slots for its initiation, does not start before all said mandatory inputs are received;

defining each of said composite data models as a construction of at least one sub data model; and

defining each of said flow rules as connecting a pair of said slots, data models and sub data models, wherein said flow rules define both data flow and process flow,

wherein said process models and data models and slots and flow rules are arranged in a structural hierarchy conforming to a set of rigid composition rules,

such that once the ~~solution~~ software application is visually defined on a display screen by the developer using the modeling language, an application model has been created, enabling a computer to execute the application model defined
5 in said modeling language without requiring further coding.

Claim 2. (currently amended) A visualizable computer executable modeling language system operating in accordance with the method of claim 1, for a complete definition of the
10 software applications, said system comprising:

process models, each of which may contain any number of sub process models, slots, data models and flow rules;

data models, each of which may contain any number of sub data models; and

15 flow rules, each of which connecting a pair of said slots, data models and sub data models, thereby defining data flow and process flow;

~~wherein said process models and data models and slots and flow rules are arranged in a structural hierarchy conforming to a set of rigid composition rules, ensuring the language system enables a computer to execute an application model defined in said modeling language.~~
20

Claim 3. (original) The modeling language system of claim 2,
25 further comprising at least one visual representation.

Claim 4. (original) The modeling language system of claim 3, wherein said visual representation comprises:

process diagrams comprising various two dimensional
30 shapes representing said process models;

sub process diagrams comprising various two dimensional shapes contained within said process diagrams, representing said sub process models;

slot diagrams comprising various two dimensional shapes situated on the edges of said process diagrams and said sub process diagrams, representing said slots;

data trees comprising hierarchical tree structures
5 contained within said process diagrams, representing said data models and said sub data models; and

flow arrows comprising arrows connecting pairs of said slot diagrams, said data trees and sub-trees of said data tress, said arrows representing said flow rules.

10

Claim 5. (previously presented) The modeling language system of claim 2, wherein each of said slots is further defined as having one of the following classifications: input slot; and output slot (exit); and further defining each of said input
15 slots as having one of the following sub-classifications: synchronous input slot (trigger); and asynchronous input slot; and further defining some of said exits as having the sub-classification terminating.

20 Claim 6. (original) The modeling language system of claim 2, wherein each of said slots is further defined as having one of the following classifications:

input slot; and

output slot (exit);

25 and further defining each of said flow rules contained in said composite process model as connecting one source and one target;

and further defining the source of each of said flow rules to be one of the following:

30 an input slot of said composite process model; an exit of a sub process model of said composite process model;

a data model of said composite process model; and

a sub data model of a data model of said composite process model;

and further defining the target of each of said flow rules to be one of the following:

an exit of said composite process model;

an input slot of a sub process model of said composite
5 process model;

a data model of said composite process model; and

a sub data model of a data model of said composite process
model.

10 Claim 7. (original) The modeling language system of claim 2,
wherein:

each of said process models may further contain a
reference to a database table (process table);

at least some of the sub data models of data models of
15 said process model are marked as interesting fields; and

each of said interesting fields further contains a
reference to a column of said process table.

Claim 8. (original) The modeling language system of claim 7,
20 wherein:

a selection condition of an SQL query (addressing clause)
may be attached to an input slot of said process model to
select matching instances of said process model each time data
is to be received by said instances through said input slot;

25 said addressing clause is defined in terms of a matching
condition between the interesting fields of said process model
and the data model of said data to be received through said
input slot.

30 Claim 9. (original) The modeling language system of claim 2,
wherein each of said process models may further contain a
reference to a computer code implementing the function of said
process model.

Claim 10. (original) The modeling language system of claim 2, wherein:

each of said composite data models is composed of said
5 sub data models by one of the following structure means:
concatenation; collection; and selection, each of said sub
data models having a classification as one of the following:
mandatory; and optional; each of said sub data models may
further be marked as recurring, with a further optional
10 indication of minimal and maximal number of occurrences;

each of said data models may further contain constraints
on the data it defines, comprising at least one of the
following: legal characters; and minimal and maximal length;
each of said data models may further comprise a set of legal
15 values and an initial value; and

each of said data models may further comprise formatting
directives.

Claim 11. (original) A modeling system for defining software
20 applications using the visualizable computer executable
modeling language system of claim 2, enabling users to create,
display, modify and test, in an integrated workspace, models
of said modeling language, in accordance with the rules of
said modeling language system, wherein: said modeling system
25 comprises a graphical user interface tool (visual modeling
tool) for creating, displaying, modifying and testing models
of said modeling language in an integrated workspace, such
that users of said modeling tool create and edit said models
using various graphical user interface (GUI) operations.

30

Claim 12. (original) The modeling system of claim 11, wherein
each of said process models and said data models is further
defined as having one of the following classifications:
dependent model: only exists as a sub model of a specific

parent model; and reusable model: may be reused as a sub model of multiple parent models, wherein each of said reusable models is assigned a unique identifier.

5 Claim 13. (original) The modeling system of claim 11, wherein models are formally represented as one of the following:

Extensible Markup Language (XML) documents;

structured database records; and any other equivalent
10 binary representation, and wherein a repository of said representations of said models, arranged as a hierarchy of packages and sub-packages (knowledge base), is used to maintain libraries of said models, and wherein the modeling system displays said models whose said representations are stored in said knowledge base, stores in said knowledge base
15 said representations of new said models that are defined by the users of the modeling system, and updates said representations of said models in said knowledge base according to modifications made to said models by said users.

20 Claim 14. (original) The modeling system of claim 11, further comprising at least the following editing capabilities: selection of editing operations from menus; adding components to said models through dragging of models from palettes of existing models; and modifying attributes of said models and
25 components of said models.

Claim 15. (previously presented) The modeling system of claim 11, wherein said workspace comprises a drawing board for displaying hierarchies of two dimensional visual diagrams,
30 each representing a corresponding said hierarchy of models, and wherein said users are able to zoom in and out from a currently displayed part of said hierarchy of diagrams, enabling the display of the details of said model and any

sub-model thereof at any desired level of said hierarchy of models.

Claim 16. (original) The modeling system of claim 11, further
5 comprising: a software program (runtime engine) to execute
models defined in said modeling language; and a visual
debugger for testing and debugging said models, wherein: said
runtime engine, as it executes said models, produces records
listing the details of said execution (trace events); said
10 trace events are used to record and store the history of said
execution; and said visual debugger uses said stored trace
events to display the current status of instances of
processes, including the content of their data, as well as
the processing steps that have led to said current status.

15

Claim 17. (previously presented) A software program (runtime
engine) to execute applications defined in the visualizable
computer executable modeling language system of claim 2,
wherein:

20 each of the applications is defined by a single said
process model and a hierarchy of its sub-models; and

the runtime engine executes the application exactly as
defined by said single process model and said hierarchy of
its sub-models, thus eliminating the need for writing
25 computer source code in any programming language to implement
the application.

Claim 18. (original) The runtime engine of claim 17, further
comprising: active models comprising objects responsible for
30 representing and enacting the definitions and rules embodied
in said models, where there is an active model corresponding
to each of said process models and data models; runtime
objects comprising objects containing the runtime state of
instances of said process models and data models, where there

may be at any time any number of runtime objects instantiated from each of said process models and data models by the corresponding said active model; and a model loader comprising an object responsible for loading said models from their formal representations stored in a repository, converting said loaded models to corresponding said active models, and caching said active models.

Claim 19. (original) The runtime engine of claim 17, wherein the runtime engine executes each of said models as a series of processing steps, wherein: each of said processing steps is triggered by the receipt of an external input; the runtime engine invokes at least one instance of at least one relevant process model to handle said received input, and executes sub-processes of said invoked processes as defined by the relevant said flow rules; and a processing step ends when any further activities to be performed depend on the receipt of other external inputs.

Claim 20. (original) The runtime engine of claim 17, wherein: the runtime engine executes each of said models as a series of processing steps by invoking at least one instance of said process models; the full state of each of said at least one process instance is made persistent at the end of each said-processing step; execution of each of said at least one process instance can resume from its stored state at any relevant time; and a repository of all said at least one process instances is available for queries and retrieval by the runtime engine while executing said models or by external applications.

Claim 21. (previously presented) A software program (code generator) to generate the code of a software program implementing the applications defined in the visualizable

computer executable modeling language system of claim 2,
wherein:

a plurality of display elements for displaying screen
objects are displayed on a display screen and components are
5 displayed corresponding to said screen objects;

each of the applications is defined by a single said
process model and a hierarchy of its sub-models; and

the code generator produces code in a general purpose
programming language implementing the application exactly as
10 defined by said single process model and said hierarchy of
its sub-models, thus eliminating the need for writing
computer source code in any programming language to implement
the application.

15 Claim 22. (original) The software program of claim 21,
wherein said general purpose programming language is Java.

Claim 23. (original) The software program of claim 21,
wherein said general purpose programming language is C++.

20

Claim 24. (currently amended) A method for overcoming the
need to write computer source code in order to develop
software applications, comprising:

creating models of the applications in a visualizable
25 computer executable modeling language system, using a visual
modeling tool, comprising:

defining each of said software applications as a hierarchy
of process models, input and output slots, data models and
flow rules;

30 classifying some of said process models and said data
models as atomic;

classifying all other process models and data models as
composite;

defining each of said composite process models as a construction of at least one of sub process models, slots, data models and flow rules;

5 defining a portion of said input slots as having one of the following sub-classifications:

mandatory; and

optional, wherein a process that requires input at its mandatory input slots for its initiation does not start before all said mandatory inputs are received;

10 defining each of said composite data models as a construction of at least one sub data model; and

defining each of said flow rules as connecting a pair of said slots, data models and sub data models, wherein said flow rules define both data flow and process flow; and

15 executing the logic defined by said created models, wherein said process models and data models and slots and flow rules are arranged in a structural hierarchy conforming to a set of rigid composition rules.

20 Claim 25. (original) The method of claim 24, wherein the execution of the logic defined by said models is made by a dedicated computer program (runtime engine).

Claim 26. (original) The method of claim 24, wherein the
25 implementation of the logic defined by said models is made by the code of a software program in a general purpose programming language, which is generated by a dedicated computer program (code generator).

30 Claim 27.(currently amended) A software development platform for overcoming the need to write computer source code in order to develop software applications, comprising:

a visualizable computer executable modeling language for the definition of software solutions, said definition comprising:

defining each of said software ~~solutions~~ applications as a
5 hierarchy of process models, input and output slots, data models and flow rules;

classifying some of said process models and said data models as atomic;

classifying all other process models and data models as
10 composite;

defining each of said composite process models as a construction of at least one of sub process models, slots, data models and flow rules;

defining a portion of said input slots as having one of the
15 following sub-classifications:

mandatory; and

optional, wherein a process that requires input at its mandatory input slots for its initiation does not start before all said mandatory inputs are received;

20 defining each of said composite data models as a construction of at least one sub data model; and

defining each of said flow rules as connecting a pair of said slots, data models and sub data models, wherein said flow rules define both data flow and process flow;

25 a visual modeling tool for defining said software solutions by at least one user as said hierarchies of models in said modeling language; and

a dedicated computer program to automatically execute said software ~~solutions~~ applications according to the logic
30 defined by said hierarchies of models, wherein said process models and data models and slots and flow rules are arranged in a structural hierarchy conforming to a set of rigid composition rules.

Claim 28. (original) The software development platform of claim 27, wherein said dedicated computer program is a runtime engine that automatically executes said software solutions at runtime, according to the logic defined by said hierarchies of models.

Claim 29. (original) The software development platform of claim 27, wherein said dedicated computer program is a code generator that automatically generates the code of a software program in a general purpose programming language implementing the logic defined by said hierarchies of models.

Claim 30. (currently amended) A computer program product comprising a computer usable medium having computer readable code embodied therein for execution on a general purpose computer, said computer usable medium storing instructions that, when executed by the computer, cause the computer to perform a modeling method for defining software applications using a visualizable computer executable modeling language, said method comprising:

providing a plurality of display elements for displaying screen objects on a display screen;

displaying components corresponding to said screen objects;

defining each of the software applications as a hierarchy of process models, input and output slots, data models and flow rules;

classifying some of said process models and said data models as atomic;

classifying all other process models and data models as composite;

defining each of said composite process models as a construction of at least one of sub process models, slots, data models and flow rules;

defining a portion of said input slots as having one of the following sub-classifications:

mandatory; and

5 optional; wherein a process that requires input at its mandatory input slots for its initiation, does not start before all said mandatory inputs are received;

defining each of said composite data models as a construction of at least one sub data model; and

10 defining each of said flow rules as connecting a pair of said slots, data models and sub

data models, wherein said flow rules define both data flow and process flow,

wherein said process models and data models and slots and flow rules are arranged in a structural hierarchy conforming
15 to a set of rigid composition rules,

such that once the ~~solution~~ software application is visually defined by the developer using the modeling language, a computer executes the application model that has been created using the computer with an appropriate display screen.